

AC 86

Self Contained Ice Machine 38 kg

Item #:
Project:
Quantity:



FEATURES

- Produces individual Gourmet crystal clear ice cubes.
- Resistant stainless steel exterior.
- Simple and reliable electromechanic controls.
- Front panel in and out airflow (air-cooled model only) for built-in installation.
- Front access condenser air filter, removable and washable (air cooled model only).
- Easily accessible front panel mount ON-OFF switch.
- Ergonomically designed ice storage access, with disappearing door. Door-closing movement dampening system.
- Water system protected by patented anti-scale system.



AC L 86
Large Gourmet 39 g
Ø 38 x H 41 mm



AC M 86
Medium Gourmet 20 g
Ø 30 x H 34 mm



AC S 86
Small Gourmet 8 g
Ø 21 x H 25 mm

CONDENSING SYSTEM

Air cooled
Water cooled

REFRIGERANT GAS

R134a

VOLTAGE V/Hz/ph

230/50/1
230/60/1

INTERNAL BIN CAPACITY

19 kg

CERTIFICATIONS



OPERATING REQUIREMENTS

	Minimum	Maximum
Air temperature	10	43
Water temperature	5	38
Water pressure	1 bar (14 psi)	5 bar (70 psi)
Electrical voltage	-10%	+10%

IMPORTANT NOTICE:
Models and specifications are subject to change without notice.
This spec sheet is meant for commercial purpose only.
For technical documentation please refer to our service manuals.

www.scotsman-ice.it
www.scotsman-ice.com


Self Contained Ice Machine 38 kg

AC 86

Self Contained Ice Machine 38 kg

Item #:
Project:
Quantity:

Self Contained Ice Machine 38 kg



UNIT DATA		SHIPPING DATA										
Size (W x D x H)		531 x 600 x 875 mm		Carton (W x D x H)		600 x 670 x 890 mm						
Net weight		44 kg		Weight		51 kg						
Version	Voltage	24 h ice production kg °C Amb. / °C Water			Energy consumption (*)		Water usage (*)	Instant power	Compressor	Circuit wires	Max. fuse size	
		10°C/10°C kg	21°C/10°C kg	32°C/21°C kg	kWh/ 100 kg	kWh/ 24h	l/h	W	W	No. x Ømm ²	A	
ACL 86 AS	230/50/1	36	34	27	37.4	10.1	5.0	550	1200	3 x 1.5	10	
ACL 86 WS	230/50/1	37	36	30	29.2	8.6	50.8	400	1200	3 x 1.5	10	
ACM 86 AS	230/50/1	38	37	31	31.0	9.4	6.0	480	1200	3 x 1.5	10	
ACM 86 WS	230/50/1	39	36	32	28.0	9.0	42.5	480	1200	3 x 1.5	10	
ACS 86 AS	230/50/1	38	37	31	35.0	10.8	5.8	480	1200	3 x 1.5	10	
ACS 86 WS	230/50/1	37	36	32	35.0	11.2	48.8	470	1400	3 x 1.5	10	
ACL 86 AS	230/60/1	36	34	27	37.4	10.1	5.0	550	1200	3 x 1.5	10	
ACM 86 AS	230/60/1	38	37	31	38.0	11.6	5.8	600	1400	3 x 1.5	10	
ACM 86 WS	230/60/1	40	40	35	31.9	11.0	47.5	500	1400	3 x 1.5	10	
ACS 86 AS	230/60/1	36	36	31	40.0	12.3	4.7	550	1400	3 x 1.5	10	
ACS 86 WS	230/60/1	37	36	32	35.0	11.2	48.8	470	1400	3 x 1.5	10	

(*) Data refer to 32°C Amb. / 21°C Water temperature conditions