## EstPak Plastik PRODUCT SPECIFICATION

Product name: Product code:	MT 54/1105 UL Black V0307	<b>Properties:</b> Material:	РР
		Measures: Capacity: Colour: Weight <b>Application:</b>	165 x 178 x 54 mm - ml. Black 18,9g ± 5% Suitable for direct contact with food
		Temperature range: Heating: Freezing:	-5°C to +100°C +70°C max 2 hours +100°C max 15 min. Usage below 0°C with
	the star	rieezing.	care. Impact force might brake the tray
		Suitable for:	Dry, aqueous, acidic, dairy and fatty content
		Handling suggestion:	If packages are stored below 0°C, it's recommended to keep containers in room temperature ≈ 24 hours before usage, to avoid damage during hanling
		Sealing options:	Heatsealable with film Suitable for MAP
		Storage recommendation:	Suggested to be stored in a dry (< 80% relative humidity) in a sealed package, protected from UV radiance
		Legislation:	See Declaration of Compliance
Packaging:			and the second
Pieces per sleeve: Sleeves per carton: Pieces per carton: Pieces per pallet: Size of carton: Carton net weight: Carton gross weight:	252 pcs 5 pcs 1260 pcs 3780 pcs 1000 x 1200 x 360 mm 23,81 kg 27,47kg	Size of pallet: Cartons per layer: Cartons per pallet: Pallet net weight: Pallet gross weight: FIN pallet weight: Pallet transport height Transportation	hight 2x0,15 m 2 pallets on top of
<b></b>		an data mata sala sa da s	each other

**Disclaimer:** It is the responsibility of our customer to determine that their use of our product is safe, lawful and technically suitable for their intended applications and markets.